

PRODUCT INFORMATION



Lubricants – Transmission Oils – Automotive

Version: 250/02a

Valvoline™ Heavy Duty Gear Oil 75W-80

Premium conventional multi-vehicle gear oil focused on Heavy Duty applications.

Mild EP gear oil is suitable for gearboxes where the manufacturer specifies GL-4 SAE 75W-80 lubricant.

Valvoline Heavy Duty Gear Oil 75W-80 provides outstanding protection and lubrication of the gearbox over a wide temperature range. The lower viscosity provides easier shifting.

Performance levels

API: GL-4

Features & Benefits

Superior protection

Superior protection against wear and tear, also under high stress working conditions. Modern additives protect against corrosion, oxidation, foam, and deposits.

Breakdown resistance

Quality base oils and a highly balanced additive system avoid breakdown situations.

Consistent viscosity

Good viscosity-temperature properties
Highly stable viscosity even at low temperatures.

Fuel Economy properties

By smooth lubrication, the product has light fuel economy properties. Easy oil circulation gives better cooling and also light fuel savings.

Applications

Suitable for hand shifted gearboxes of trucks and buses and other equipment where the manufacturer recommends GL-4 transmission oil with a viscosity of SAE 75W-80.

This product can be used in many models of the mentioned equipment brands and more, but always check first the *Owners Manual* or the *Valvoline Oil Advisor* on www.valvolineurope.com before use.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline Heavy Duty Gear Oil	
SAE Viscosity Grade	75W-80
Viscosity , mm ² /s @ 100 °C. ASTM D-445	9,6
Viscosity , mm ² /s @ 100 °C. After shearing (CEC: L-45-T-93).	Stay-in-grade
Viscosity , mm ² /s @ 40 °C. ASTM D-445	47,5
Viscosity Index ASTM D-2270	192
Viscosity , mPa.s -40°C. ASTM D-5293	<150.000
Pour Point, °C ASTM D-5950	-42
Specific Gravity @ 15.6°C. ASTM D-4052	0,862
Flash Point, COC, °C. ASTM D-92	208

**This information only applies to products manufactured in the following location(s):
Europe**

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet <http://msds.valvoline.com>

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces – 250/01a

™ Trademark of Valvoline, registered in various countries © 2016

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.